

# **HIPPO PRO<sup>®</sup>**

**MULTI-PURPOSE  
TOOLS  
FOR PLANET  
EARTH'S  
TOUGHEST  
JOBS**



**FEATURE & BONDING GUIDE ON REVERSE**

## FEATURE & BONDING GUIDE

	<b>PRO 3</b>	<b>PRO 2</b>	<b>PRO 1</b>
Solvent Free	●	●	●
Contains No VOC's	●	●	●
Interior & Exterior Use	●	●	●
Grab Power (When Bonding)	<b>ULTIMATE TACK</b>	<b>HIGH TACK</b>	<b>INSTANT GRAB</b>
Vibration Resistant	●	●	●
Overpaintable	●	●	●
Use As A Gap Filler	●	●	●
Can Be Used On Damp Surfaces	●	●	●
Can Be Used To Seal Flexible Joints	●	●	●
Dries Permanently Flexible	12.5%	25%	
Dries Completely Underwater	●	●	
Waterproof When Dry	●	●	
UV Light Resistant	●	●	
Resistant To Chemicals	●	●	
Skin Time (Touch Dry)	<b>FROM 10 MINS</b>	<b>FROM 20 MINS</b>	<b>FROM 60 MINS</b>
Full Cure Time (Normal Conditions)	<b>24 HOURS</b>	<b>24 HOURS</b>	<b>24-48 HOURS</b>
Temperature Resistant	<b>-50° to +150°</b>	<b>-50° to +150°</b>	<b>-10° to +70°</b>
Meets ISO11600 F25LM	<b>CLEAR ONLY</b>	●	
Can Be Used As Sandable Filler	●		
Wood	●	●	●
Plaster	●	●	●
Plasterboard	●	●	●
Polystyrene	●	●	●
Brick	●	●	●
Concrete	●	●	●
Ceramic Tiles	●	●	●
Most Metals	●	●	●
Natural Stone (Including Granite & Marble)	●	●	●
Plastics	●	●	
Glass	●	●	
Lead	●		
Fibreglass	●		
Carbon Fibre	●		

Intended as a guide only - Environmental conditions can effect performance